Siemens 6ES7314-6CH04-0AB0 SIMATIC S7-300 CPU 314C-2 DP



Siemens 6ES7314-6CH04-0AB0 is the SIMATIC S7-300 CPU 314C-2 DP. The 314C-2 DP combines built-in discrete and analog channels with a dedicated PROFIBUS DP connection. The CPU runs the control program, handles onboard signals and exchanges data with distributed DP stations.

Technical Specifications

Product Identity	
Manufacturer	Siemens AG
Complete order number	6ES7314-6CH04-0AB0
Product family	SIMATIC S7-300
CPU designation	CPU 314C-2 DP
Data-sheet revision baseline	Hardware 01 / firmware V3.3
Housing (W × H × D)	120 × 125 × 130 mm
Approximate weight	680 g
Functional Configuration	
Communications	MPI and PROFIBUS DP
Signal arrangement	24 DI, 16 DO, 4 AI, 2 AO and 1 Pt100
High-speed counters	4 counters, up to 60 kHz
Engineering software	STEP 7 V5.5 SP1 or V5.3 SP2 with HSP 203
Performance & Power	
Integrated work memory	192 KB
Rated supply	24 V DC
Permissible supply range	19.2–28.8 V DC
Rated current	880 mA
Typical no-load current	150 mA
Typical inrush current	5 A
Typical power loss	13 W
Typical bit operation	0.06 µs
Typical floating-point operation	0.59 µs
Environment	
Horizontal mounting	0 to 60 °C
Vertical mounting	0 to 40 °C

Celine | unity@mvme.cn | +86-18020776786

Compatibility & Selection Guide

Engineering baseline. Configure the exact CPU 314C-2 DP hardware entry with STEP 7 V5.5 SP1 or V5.3 SP2 with HSP 203. Onboard and distributed signals. Retain the project's assignments for the onboard I/O and configured DP stations. The PtP and PN/DP versions use different communications hardware.

Wiring & Installation Reference

CPU supply (24 V DC), MPI (RS-485), PROFIBUS DP (Isolated RS-485), Local field I/O (Front connector). Use the 19.2–28.8 V DC operating supply range for the CPU. Two 40-pin front connectors.

Frequently Asked Questions

How large a Micro Memory Card can 6ES7314-6CH04-0AB0 use?

It accepts a SIMATIC Micro Memory Card up to 8 MB as load memory.

How much retentive data can 6ES7314-6CH04-0AB0 preserve on a power interruption?

The maximum retentive data area is 64 KB. Allocate the values that must survive a power interruption within that limit.

How many diagnostic events can 6ES7314-6CH04-0AB0 retain for fault finding?

The diagnostic buffer has up to 500 entries, with the last 100 entries retained after power loss.

How long does the real-time clock of 6ES7314-6CH04-0AB0 keep time without power?

Clock backup time is six weeks at an ambient temperature of 40 °C.

How many S7-300 racks can 6ES7314-6CH04-0AB0 address in one local assembly?

The configuration supports up to four racks in total, including the central rack.

What block-count limit should a project migration to 6ES7314-6CH04-0AB0 allow for?

The CPU supports up to 1,024 DBs, FCs and FBs combined. The selected memory card can reduce the number that can actually be loaded.

How many connections can be allocated to programming devices on 6ES7314-6CH04-0AB0?

The configurable allocation for PG communication is 1 to 11 connections.

Which startup organization block can 6ES7314-6CH04-0AB0 execute?

Startup logic runs in OB 100. The CPU supports one startup organization block.

Source: Siemens exact-order datasheet. Selected manufacturer page follows.

Celine | unity@mvme.cn | +86-18020776786

SIEMENS

Product data sheet 6ES7314-6CH04-0AB0



SIMATIC S7-300,
CPU 314C-2 DP COMPACT CPU WITH MPI,
24 DI/16 DO, 4AI, 2AO, 1 PT100,
4 FAST COUNTERS (60 KHZ),
INTEGRATED DP INTERFACE,
INTEGRATED 24V DC POWER SUPPLY,
192 KBYTE WORKING MEMORY,
FRONT CONNECTOR (2 X 40PIN) AND MICRO MEMORY CARD REQUIRED

-

General information	
Hardware product version	01
Firmware version	V3.3
Engineering with	
Programming package	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203
Supply voltage	
24 V DC	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
External protection for supply cables (recommendation)	Miniature circuit breaker, type C; min 2 A; miniature circuit breaker type B, min. 4 A
Mains buffering	
Mains/voltage failure stored energy time	5 ms
Repeat rate, min.	1 s
Digital inputs	
Load voltage L+	
Rated value (DC)	24 V
Reverse polarity protection	Yes

© Copyright Siemens AG 2013